



## NBL75BVZ17

The rearTWIST HD Large BNC cable connector is designed for large cable diameters as used on long runs and high data rates (HD).

Like all Neutrik BNCs it offers a true 75  $\Omega$  design and is perfectly suitable for HD applications. The patented rearTWIST boot guarantees easy access even in high density applications.

Suitable cables:

Belden 7731A (ANH), CAE HD16720LSZH, Draka 1.6/7.3AF, RG 11, Klotz V16/72, Canford SDV-HD, Nexans HF 75 1,6/7,2 02Y(ST)C(ST)H, Percon VK9, Tesca Sphere

Crimp size:

Pin: 1.8 mm

Shield: 10.0 mm (hex)

## Features & Benefits

- "rearTWIST Principle" locking/unlocking using the easily accessible soft touch boot (Patent DE 100 48507)
- True 75  $\Omega$  design meets the stringent HDTV / DVD requirements
- Snug-fit center pin insert provides tactile feedback
- Excellent cable protection and retention
- Accessories include crimp tool and dies
- Ideal for recessed bulkheads where access to the "head" of the connector might be an issue. These connectors turn from the back and not the front.
- Leading area: Avoids tilting due to side forces to protect contacts from deformation. Guarantees a lifetime of min. 1000 mating cycles!
- Shield and jacket crimp technology prevents the problem of an exposed grounding braid on cable assemblies
- Precise Swiss machined brass parts for outstanding durability

Technical Information

Product	
Title	NBLC75BVZ17
Connection Type	BNC 75 Ω
Gender	male

Electrical	
Contact resistance	≤ 3 mΩ (inner)
Contact resistance	≤ 2 mΩ (outer)
Dielectric strength	1,5 kVdc
Impedance	75 Ω
Insulation resistance	> 5 GΩ
Rated voltage	<50 V
VSWR	≤1.050/>32 dB up to 1 GHz ≤1.065/>30 dB up to 2 GHz ≤1.100/>26 dB up to 3 Ghz

Mechanical	
Cable O.D.	10.4 mm
Cable retention	> 30 N (Center)
Crimp size	10.0 mm (HEX)
Crimp size (pin)	1.8 mm
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Wiresize	
Locking device	Bayonett
Cable anchoring	Jacket crimping

Material	
Contacts	Brass (CuZn35Pb2), 0.2 µm AuCo (Center contact)
Insert	PTFE
Shell	Brass (CuZn39Pb3)
Shell plating	Optalloy®

Environmental	
Temperature range	-30 °C to +85 °C
Contact crimpability	Complies with IEC 60803 and IEC 60352-2