NBNB75GUU11

BNC cable jack for panel mount, grounded

Neutrik's BNC cable jacks for panel mount offer a true 75 Ω design for serial and digital (HD) signals. The machined brass connector body provides an extremely rugged and non-abrasive connection over long term use.

Suitable cables:
Argosy Image 1000, Draka 1.0/4.8AF, Draka 755-901/5, Klotz V10/48

Crimp size:
Pin: 1.6 mm (square)
Shield: 7.36 mm (hex)

Features & Benefits

- Gold plated center contact
- Grounded panel mount
- True 75 Ω design meets the stringent HD requirements

All rights reserved / 29.04.2024

NEUTRIK

Technical Information

Product	
Title	NBNB75GUU11
Connection Type	BNC 75 Ω
Gender	female

Electrical	
Contact resistance	≤ 3 mΩ (inner)
Contact resistance	≤ 2 mΩ (outer)
Dielectric strength	1,5 kVdc
Impedance	75 Ω
Insulation resistance	> 5 GΩ
Rated voltage	<50 V
VSWR	≤1.050/>32 dB up to 1 GHz ≤1.065/>30 dB up to 2 GHz ≤1.100/>26 dB up to 3 Ghz

All rights reserved / 29.04.2024

NEUTRIK

Mechanical

Cable O.D.	7.3 mm
Cable retention	> 30 N (Center)
Crimp size	7,36 Hex crimp (shield) acc. MIL22520/5-41(A)
Crimp size (pin)	1,6 Square crimp (pin) acc. IEC 60803 (die designation 2)
Insertion force	< 25 N
Lifetime	> 1000 mating cycles
Wiresize	
Locking device	Bayonett
Mounting direction	Rear mounting
Chassis shape	12.7 mm
Cable anchoring	Jacket crimping

Material

Contacts	Brass (CuZn35Pb2), 0.2 µm AuCo (Center contact)
Insert	PTFE
Shell	Brass (CuZn39Pb3)
Shell plating	Optalloy®

Environmental

Temperature range	-30 °C to +85 °C
Contact crimpability	Complies with IEC 60803 and IEC 60352-2

All rights reserved / 29.04.2024