



## NC3FXCC

### PHASE OUT

3 pole female cable connector, RF-protected, gold contacts

Cable O.D.: 5.4 - 6.2 mm

Crimp Size Shield: 6.5 mm (hex)

The XCC XLR cable connector Series with circumferential shield contact provides excellent RF-protection to transmit digital audio signals most efficient and reliable. This XLR features a coaxial ground spring and a coaxial hex crimp ferrule at the cable entrance for proper and reliable transition of the shield to the shell.

## Features & Benefits

- 3 pole cable connector with a circumferential shield contact for best EMI protection
- Rugged zinc diecast shell, long lasting and durable
- Boot with rubber gland gives high protection against bending stresses
- XCCR coding ring to indicate digital AES signals included
- Chuck type strain relief system for secure clamping of cables

Technical Information

Product	
Title	NC3FXCC
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 3 mΩ
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	16 A
Rated voltage	< 50 V
Shielding effectiveness	> 55 dB @ 1.3 GHz

Mechanical	
Cable O.D.	5.4 - 6.2 mm
Crimp size	6,47 Hex crimp (shield) acc. IEC 60803 (die designation E)
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock

**Material**

<b>Boot</b>	Polyurethan
<b>Coding Ring</b>	PA 6 15% GR
<b>Contact plating</b>	0.2 µm Au hard alloy over 2 µm Ni
<b>Contacts</b>	Bronze (CuSn8)
<b>Crimp ferrule</b>	CuZn39Pb3, Ni plated
<b>Insert</b>	Polyamide (PA66)
<b>Locking element</b>	St3K32 (latch) / Ck 67 (spring)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell plating</b>	Nickel
<b>Strain relief</b>	Polyacetal (POM)
<b>Circumferential ground spring</b>	CuSn6, Ni plated

**Environmental**

<b>Approvals</b>	UL
<b>Flammability</b>	UL 94 V-0
<b>Standard compliance</b>	IEC 61076-2-103
<b>Protection class</b>	IP 40
<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-30 °C to +80 °C