



NC3MD-H-B

3 pole male receptacle, horizontal PCB mount, black metal housing, gold contacts

Universal D-size metal body XLR panel mount series for pcb mount applications. Insert is removable from shell for ease assembling. UL recognized component.

Features & Benefits

- D-shape metal shell
- Optimal RF protection using 3 shield contacts
- Insert is removable from rear of connector and locked into place by internal latch - permitting assembling and testing of pcb before assembling into housing
- Front or rear panel mount

Technical Information

| Product | |
|-----------------|-----------|
| Title | NC3MD-H-B |
| Connection Type | XLR |
| Gender | male |

| Electrical | |
|------------------------------|---------------------------------|
| Capacitance between contacts | $\leq 4\text{ pF}$ |
| Contact resistance | $\leq 5\text{ m}\Omega$ |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | $> 10\text{ G}\Omega$ (initial) |
| Rated current per contact | 6 A |
| Rated voltage | $< 50\text{ V}$ |

| Mechanical | |
|--------------------|------------------------|
| Insertion force | $\leq 20\text{ N}$ |
| Withdrawal force | $\leq 20\text{ N}$ |
| Lifetime | > 1000 mating cycles |
| Wiresize | |
| Wiring | Horizontal PCB mount |
| Locking device | Latch lock |
| Mounting direction | Rear mounting |
| Chassis shape | D |

| Material | |
|-----------------|-----------------------------------|
| Contact plating | 0.2 µm Au hard alloy over 2 µm Ni |
| Contacts | Brass (CuZn35Pb2) |
| Insert | PA66 |
| Locking element | Steel Ck67 |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Black chromium |

| Environmental | |
|---------------------|---------------------------|
| Approvals | UL |
| Flammability | UL 94 V-0 |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |