



## NE8FAV-YK

Panel mount RJ45 receptacle with IDC terminals, A-Series cutout with latch lock, max. panel thickness 3 mm. Mounting screws included.

The etherCON Series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lightning network applications. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry.

The all plastic A-Series offers the most space saving and cost effective design.

Attention! Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S\* cables.

### Features & Benefits

- Accommodates rugged etherCON NE8MC\* or any standard RJ45 plug
- Most space saving and cost effective design
- Selectable ground - panel connection
- PoE type 3 class 6 (60W) acc. IEEE 802.3bt
- Approved latch lock system
- CAT5e / Class D according to TIA/EIA 568C and ISO/IEC 11801
- Easy and quick mounting using Krone punch down terminals

Technical Information

| Product |           |
|---------|-----------|
| Title   | NE8FAV-YK |
| Gender  | female    |

| Electrical                |   |
|---------------------------|---|
| Contact resistance        | < 50 mΩ   |
| Dielectric strength       | 1 kVdc  |
| Frequencyrange            | 1 - 100 MHz   |
| Insulation resistance     | > 0.5 GΩ  |
| Rated current per contact | 1,5 A   |
| Rated voltage             | ≤ 57 V  |
| Transmission performance  | CAT5e acc. to TIA/EIA 568C channel specifications<br>CLASS D acc. to ISO/IEC 11801 channel specifications |
| Power over Ethernet       | PoE type 3 class 6 (60W) acc. IEEE 802.3bt  |

**Mechanical**

|                    |                            |
|--------------------|----------------------------|
| Insertion force    | ≤ 20 N                     |
| Withdrawal force   | ≤ 20 N                     |
| Lifetime           | > 1000 mating cycles       |
| Panel thickness    | max. 3 mm 0.12'            |
| Wiresize           | 0.14 - 0.5 mm <sup>2</sup> |
| Wiresize           | 26 - 20 AWG                |
| Locking device     | Latch lock                 |
| Mounting direction | Rear mounting              |
| Chassis shape      | A                          |
| Mounting           | A-Screw                    |

**Material**

|                 |                           |
|-----------------|---------------------------|
| Contact plating | 0.2 µm Au over Ni plating |
| Contacts        | Bronze (CuSn8)            |
| Insert          | PBTP 15 % GR              |
| Shell           | PBTP 15 % GR              |
| Strain relief   | CuZn35Pb2, Tin plated     |

**Environmental**

|                     |   |
|---------------------|---|
| Flammability        | UL 94 V-0   |
| Temperature range   | -30 °C to +80 °C  |
| Standard compliance | ISO/IEC 11801-1 Ed. 1.0 (2017-11)<br>IEC 60603-7-3 Ed.2.0 (2010-04)<br>IEC 60512-99-002 Ed.2.0 (2022-01)<br>IEC 60512-9-3 (2011-06) |