



## SCDX

This hinged cover seals D-size chassis connectors from water, dust and dirt in unmated condition according to IP42. It is available in different colors.

SCDX – black (if used with opticalCON, black indicates multi-mode)

SCDX-5 – green (if used with opticalCON, green indicates single-mode APC)

SCDX-6 – blue (if used with opticalCON, blue indicates single-mode PC)

SCDX-9 – white (e.g. walloutlet)

Suitable for:

XLR D Series female

XLR D Series male

1/4" Jacks D Series

speaKON NL2M\* and NL4M\*

powerCON 20 A Series NAC3MPA\* and NAC3MPB\*

powerCON TRUE1 NAC3MPX

USB NAUSB-W\*

HDMI NAHDMI-W\*

D-SUB NADB\*

Firewire NA1394-6-W\*

etherCON A&B Series

etherCON D Series

etherCON CAT6 Chassis Connectors

BNC D Series

Phono (RCA) Chassis Connectors

Technical Information

| Product |      |
|---------|------|
| Title   | SCDX |

| Mechanical |  |
|------------|--|
| Wiresize   |  |

| Material      |      |
|---------------|------|
| Sealing cover | PP-R |

| Environmental     |                |
|-------------------|----------------|
| Flammability      | UL 94 HB       |
| Temperature range | -30° to +80 °C |