

## NA-20-DLINE

Connect your legacy audio gear to the DANTE® world. The Line I/O to DANTE® Interface is an end-of-network device. It is a breakout box which allows two channels of audio to be integrated into a DANTE® network. Simultaneously, NA-20-DLINE converts a DANTE® stream into analog audio signals. Hence, it is possible to use this tiny box to feed analog audio signals into the DANTE® network while at the same time receiving a mix from another DANTE® source.

Line I/O to DANTE® Interface is designed for harsh stage conditions. It therefore features lockable chassis connectors for both the audio and network connections. For fixed installations, the rubber protection can be removed. With optional mounting brackets or a rack panel, the box can be mounted below tables, in floor boxes, or in equipment racks.



- Connect analog audio equipment to a Dante® network
- AES67 compliant
- Enhanced ESD Protection
- Extremely robust and compact design for rugged stage conditions
- Requires a Power over Ethernet switch or a PoE injector (802.3 af/at; class 1)
- Feed non Dante® ready amplifiers, speakers or mixing desks with signals from the Dante® network
- Improved Audio Parameters
- LED Ring for Status Indication
- Rack mountable

## Technical Information

Product	
<b>Title</b>	NA-20-DLINE
<b>Product family</b>	Line Out to Dante Interfaces

Electrical	
<b>Power consumption</b>	< 2 watts
<b>Power supply</b>	PoE switch (Power over Ethernet) or PoE injector (according to IEEE 802.3af/at/bt)

Mechanical	
<b>Weight</b>	0.44 kg (1 pound)
<b>Dimensions (with rubber protection)</b>	l = 164 mm (6.3 inches) w = 82 mm (3.2 inches) h = 51 mm (2.0 inches)
	l = 151 mm (5.9 inches) w = 66 mm (2.6 inches) h = 41 mm (1.6 inches)

Environmental	
Standard compliance	REACH EC 1907/2006 Directive 2011/65/EU IEC 62368-1:2018 IEC 62368-1:2023 EN IEC 62368-1:2020+A11:2020 UL 62368-1:2019 UL 62368-1:2021 CSA C22.2 No. 62368-1:19
Ingress protection class	IP20
Temperature range	-5°C to +60°C
Storage temperature	-40°C to +150°C

Dante specifications	
Channels	2 OUTPUTS (line level)
Supported sampling rates	44.1 / 48 / 88.2 / 96 kHz
Bit depth	16, 24 and 32 Bit
Latency	Depending on the network configuration, 1 ms (standard)
Ethernet connection	100 BASE-TX (PoE support)

Analog audio output	
Output impedance	< 150 Ohm
Output level (balanced)	24 dBu max.
Frequency response	20 Hz to 20 kHz (+/-0.5 dB)
Dynamic range	> 100 dB
Signal-to-noise ratio	> 108 dB
THD + noise	< 0.01 % @ + 4 dBu, A-weighting
Crosstalk	-100 dB @ 20 kHz