



## NADB15FF

15 pole D-SUB feedthrough, female to female, D-shape nickel housing

### Features & Benefits

- Ideal for audio networking and integration of equipment into video systems
- Universally accepted standard D-shape housing

## Technical Information

| Product |                 |
|---------|-----------------|
| Title   | NADB15FF        |
| Gender  | female - female |

| Electrical                    |            |
|-------------------------------|------------|
| Contact resistance            | 30 mΩ      |
| Insulation resistance         | > 5 GΩ     |
| Number of electrical contacts | 15         |
| Rated current per contact     | 3 A        |
| Rated voltage                 | 50 V ac    |
| Dielectric strength           | > 0.5 kVac |

| Mechanical         |                |
|--------------------|----------------|
| Panel thickness    | 4 mm           |
| Wire size          |                |
| Wiring             | Feedthrough    |
| Mounting direction | Front mounting |
| Chassis shape      | D              |

| Material        |                         |
|-----------------|-------------------------|
| Contact plating | Au                      |
| Contacts        | Brass (Pb-free)         |
| Insert          | Steel , tin plated, PBT |
| Shell           | Zinc diecast (ZnAl4Cu1) |
| Shell plating   | Nickel                  |

| Environmental     |                  |
|-------------------|------------------|
| Flammability      | UL 94-V0         |
| Temperature range | -25 °C to +85 °C |