



## NC3FX-SPEC.

Solid 3 pole female cable connector with locking ring for highest security of connection and uninterrupted RF-screening.

Female XLR cable connector with solid `coax` shell. A small grub screw can make the connection to the microphone and Gooseneck quasi theft proof. Black metal housing with gold contacts.

### Features & Benefits

- Solid female cable connector with locking ring for highest security of connection
- Protects against accidental disconnects
- Avoids movements and noises
- Chuck type strain relief system for secure clamping of cables
- Uninterrupted EMI protection
- Thief-prove, grub screw secure connector onto microphone or gooseneck
- Rugged zinc diecast shell, long lasting and durable
- Boot with rubber gland gives high protection against bending stresses

## Technical Information

Product	
Title	NC3FX-SPEC.
Connection Type	XLR
Gender	female

Electrical	
Capacitance between contacts	$\leq 4$ pF
Contact resistance	$\leq 3$ m $\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10$ G $\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	$< 50$ V

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	$\leq 20$ N
Withdrawal force	$\leq 20$ N
Lifetime	$> 1000$ mating cycles
Wiresize	max. 2.5 mm <sup>2</sup>
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Locking nut

Material	
Boot	Polyurethan
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA66)
Locking element	St3K32 (latch) / Ck 67 (spring)
Shell	Zinc diecast (ZnAl4Cu1)
Shell coating	Black KTL
Strain relief	Polyacetal (POM)
Securing Ring	Brass (CuZn39Pb3)

Environmental	
Approvals	UL
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C