



NC7FD-LX-B

7 pole female receptacle, solder cups, black metal housing, gold contacts

The DLX series features a compact all metal housing with an ingenious duplex ground contact, which offers excellent RF protection and shielding.

Features & Benefits

- ✓ All metal housing offers best overall RF protection and electromagnetic shielding
- ✓ Duplex ground contact for excellent contact integrity between chassis and cable connector
- ✓ Female contact incorporates a solder barrier to prevent solder running into the contact mating area
- ✓ Larger solder contacts for easier termination
- ✓ Optional connection to easily join pin1 to chassis ground
- ✓ D-style housing provides installation compatibility with industry standard D mounting dimensions

Technical Information

| Product | |
|-----------------|------------|
| Title | NC7FD-LX-B |
| Connection Type | XLR |
| Gender | female |

| Electrical | |
|------------------------------|----------------------------------|
| Capacitance between contacts | $\leq 9 \text{ pF}$ |
| Contact resistance | $\leq 5 \text{ m}\Omega$ |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | $> 10 \text{ G}\Omega$ (initial) |
| Rated current per contact | 5 A |
| Rated voltage | $< 50 \text{ V}$ |

| Mechanical | |
|------------------|-------------------------|
| Insertion force | $\leq 20 \text{ N}$ |
| Withdrawal force | $\leq 20 \text{ N}$ |
| Lifetime | > 1000 mating cycles |
| Wiresize | max. 1.0 mm^2 |
| Wiresize | max. 18 AWG |
| Wiring | Solder contacts |
| Locking device | Latch lock |
| Chassis shape | D |

| Material | |
|-------------------------|----------------------------|
| Contact plating | 2 µm Au over 2 µm Ni |
| Contacts | Brass (CuZn39Pb3) |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Locking element | Steel Ck67 |
| Locking element plating | Nickel |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell coating | Black KTL |

| Environmental | |
|---------------------|---------------------------|
| Flammability | UL 94 HB |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |