



NPPA-TT-IDC

2 x 48 TT (Bantam) jacks, half normalled bottom row, fast and easy change of normalling with jumpers, 288 Krone-type IDC terminals, individual grounding

All NPPA patch panels are fitted with high quality, long life NJ3TTA gold plated double contact jacks (2x48), featuring best contact integrity. The unit, robustly housed in a black coated steel shell, is finished off with a built in cable bar and two large channel identification strips for perfect management of the system. The NPPA patch panels are an innovative and compact patching system (just 1U high) for 19" rack mounting.

Features & Benefits

- Innovative and compact patching system (just 1U high) for 19" rack mounting
- Robustly housed in a black coated steel shell
- High quality long life gold plated Neutrik prewired double jacks with best contact integrity
- Qualified for analog and digital signals acc. AES3, 48 kHz sampling frequency
- Convenient change of normalling with the aid of jumpers
- Flexible grounding system (see Assembly Instruction)

Technical Information

| Product | |
|-----------------|-------------|
| Title | NPPA-TT-IDC |
| Connection Type | Patch Panel |

| Electrical | |
|-----------------------|--|
| Signal Type | Digital suitability acc. AES/EBU (3.072 Mb/s and 6.144 Mb/s) |
| Contact resistance | 20 m Ω |
| Contact resistance | < 25 m Ω |
| Dielectric strength | 1 kVdc |
| Frequencyrange | DC to > 50 MHz |
| Insulation resistance | > 1 G Ω |
| Channel separation | > 100 dB @ 10 kHz, 600 terminated > 40 dB @ 6 MHz, 110 terminated |

| Mechanical | |
|------------------|----------------------|
| Insertion force | < 10 N |
| Withdrawal force | > 8 N |
| Lifetime | > 5000 mating cycles |
| Wiresize | |
| Locking device | Retention spring |

| Material | |
|-----------------|--|
| Contact plating | TRIBOR® (0.2 µm AuCo over 2 µm NiP) (Jacks) |
| Contacts | Bronze (CuSn6) (Jacks) |
| Shell | PA 66 blend (Jacks) |
| Shell plating | Black |
| Front panel | AlMgSi0.5 F22 |

| Environmental | |
|-------------------|------------------|
| Temperature range | -30 °C to +80 °C |