



NYS-SPCR

Module with switching contacts for NYS-SPP-L.
Solution for insert jack of mixing consoles, Split
print by-passes the use of a special wired Y-Cable

Technical Information

| Product | |
|-----------------|-------------|
| Title | NYS-SPCR |
| Connection Type | Patch Panel |

| Electrical | |
|-----------------------|--|
| Signal Type | AES/EBU Signals (digital) |
| Contact resistance | < 10 mΩ |
| Contact resistance | < 10 mΩ |
| Dielectric strength | 1 kVdc |
| Frequencyrange | DC to > 50 MHz |
| Insulation resistance | > 1 GΩ @ 500 V dc |
| Channel separation | > 100 dB @ 10 kHz, 600 terminated > 40 dB @ 6 MHz, 110 terminated |
| Handles Phantom Power | Yes |

| Mechanical | |
|------------------|-----------------------|
| Insertion force | < 20 N |
| Withdrawal force | > 10 N |
| Lifetime | > 10000 mating cycles |
| Wiresize | |
| Locking device | Retention spring |

| Material | |
|----------|--------------------------------------|
| Contacts | Bronze, tin plated (Switch contacts) |
| Shell | ABS (Jacks) |

| Environmental | |
|-------------------|------------------|
| Temperature range | -30 °C to +80 °C |