# Power Bar X NPBSX-T1-B3 (US)

**Power Bar Xtreme. 1x powerCON®TRUE1® IN – 3x NEMA 5-20R OUT**

The Power Bar is an ultra-compact powerCON TRUE1 distribution box designed for professionals. Its innovative injection-molded housing offers exceptional mechanical protection, combined with high cost-efficiency. With a rugged, space-saving design, it is the ideal solution for demanding, harsh environments. 1x powerCON®TRUE1® IN and 3 x NEMA 5-20R OUT.








All rights reserved / 28.11.2026

NEUTRIK

## Features & Benefits

- **Ultra-compact injection-molded power distribution box for harsh applications**
- **High durability and safety:** Impact-resistant (high IK rating), non-conductive, flame-retardant polymer housing (V0), UV-resistant material (UL 746C F1 certified), high temperature resistance, high impact strength
- **Flexible mounting options:** powerBAR truss clips, screw and Velcro strap mounting holes
- **Standards compliance:** Fully compliant with U.S. regulations
- **Attractive pricing**

### Market & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

## Article Varations

| Article name | Details | Order code |
|---|---|---|
| NPBSX-T1-B3 | IN: 1 x powerCON®TRUE1® - OUT: 3 x NEMA 5-20R | 1041167 |

## Technical Information

| Product | |
|---|---|
| Input device | Input device 1x powerCON®TRUE1® (NAC3MPX-TOP) |
| Output device | 3x NEMA 5-20R |


All rights reserved / 28.11.2026

NEUTRIK

| Electrical | |
|---|---|
| Contact resistance / protection class | Protection class II |
| Dielectric strength | 0,5 kV / mm |
| Rated Voltage and Current | UL: 20 A, 120 VAC |
| Number of electrical contacts | 2 + PE |
| Phases | single-phase |

| Mechanical | |
|---|---|
| Mechanical impact resistance | IK9 |
| Dimensions | 245 x 60 x 69 mm |
| Conductor cross section | AWG12 |
| Weight | 0.65 kg |
| Mounting options | Mounting options Truss clip and mounting holes for securing or suspending with screws or Velcro |

| Material | |
|---|---|
| Housing | Polymer composite |
| Color | black |

| Environmental | |
|---|---|
| Standards compatibility | Housing material with UL 94 V-0 flammability rating and UL 746C F1 UV resistance rating |
| Standard compliance | UL 1640 certification in progress |
| Protection class | IP20/ NEMA1 |
| Temperature range | -25 °C to +70 °C |


All rights reserved / 28.11.2026