Power Bar XO NPBSX-T1-T3 (EU+US)



Power Bar Xtreme. 1x powerCON®TRUE1® IN – 3x powerCON®TRUE1® OUT

The Power Bar is an ultra-compact powerCON TRUE1 distribution box designed for professionals. Its innovative injection-molded housing offers exceptional ingress and mechanical protection, combined with high cost-efficiency. With a rugged, space-saving design, it is the ideal solution for demanding, harsh environments. 1x powerCON®TRUE1® and 3 x powerCON®TRUE1®





All rights reserved / 28.11.2026



Features & Benefits

- **Ultra-compact injection-molded power distribution box for harsh applications**
- **High durability and safety:** Impact-resistant (high IK rating), non-conductive, flame-retardant polymer housing (V0), UV-resistant material (UL 746C F1 certified), high temperature resistance, high impact strength
- **Flexible mounting options:** powerBAR truss clips, screw and Velcro strap mounting holes
- **Standards compliance:** Fully compliant with EU and U.S. regulations
- **Attractive pricing**

Market & Applications

- Markets: Professional video wall / lighting / audio
- Mobile application: Festivals, live events
- Semi-permanent applications: Theaters, studios

All rights reserved / 28.11.2026

NEUTRIK

Article Variations

Article name	Details	Order code
NPBSX-T1-T3	IN: 1x powerCON®TRUE1® -OUT: 3 x powerCON®TRUE1®	1041279

Technical Information

Product	
Input device	1x powerCON®TRUE1® (NAC3MPX-TOP)
Output device	3x powerCON®TRUE1® (NAC3FPX-TOP)

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated Voltage and Current	CE: 16 A, 250 VAC; UL: 20 A, 250 VAC
Number of electrical contacts	2 + PE
Phases	single-phase

Mechanical	
Lifetime	> 5000 Mating cycles per connector
Mechanical impact resistance	IK9
Dimensions	245 x 60 x 69 mm
Conductor cross section	AWG12
Weight	0.65 kg
Mounting options	Truss clip and mounting holes for securing or suspending with screws or Velcro

All rights reserved / 28.11.2026

Material	
Housing	Polymer composite
Color	black

Environmental	
Standards compatibility	Housing material with UL 94 V-0 flammability rating and UL 746C F1 UV resistance rating
Standard compliance	CE Declaration; UL 1640 certification ; CSA C22.2#300 certification
Protection class	IP20/ NEMA1
Temperature range	-25 °C to +70 °C

All rights reserved / 28.11.2026