

Professional DMX AES/EBU Cable Assemblies

2 × 0.22 mm² / AWG24 or 2 × 0.34 mm² / AWG22
with 3- or 5-pin XLR connectors



When flawless signal transmission is critical—on stage, in the studio, or across complex installations—the **NEUTRIK® Professional DMX AES/EBU Cable Assemblies** deliver exactly what professionals need. Designed for digital lighting control (DMX512/DMX512-A) and digital audio interconnects (AES/EBU), these cable assemblies ensure stable, interference-resistant performance in any professional environment.



Whether you're managing moving lights in a live show, integrating a theatre lighting grid, or routing audio control data in a broadcast facility, these assemblies provide **extreme reliability** with the build quality and signal consistency expected from Neutrik.





Features & Benefits

- ✓ **DMX512 & AES/EBU compliant**
- ✓ **Excellent EMC protection with dual shield (foil + braid) or high-coverage spiral shield**
- ✓ **Low capacitance & high signal integrity over long distances**
- ✓ **PVC jacket with high flexibility**
- ✓ **Available in standard lengths (0.5 m to 50 m) or custom on request**

Article Variants

Article name	Details	Order code
NKX3D122-X1X1-M0050	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 0.5m; Connectors: NC3FXX-B & NC3MXX-B	1039626
NKX3D122-X1X1-M0100	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 1m; Connectors: NC3FXX-B & NC3MXX-B	1039627
NKX3D122-X1X1-M0150	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 1.5m; Connectors: NC3FXX-B & NC3MXX-B	1039628
NKX3D122-X1X1-M0300	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 3m; Connectors: NC3FXX-B & NC3MXX-B	1039629
NKX3D122-X1X1-M0500	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 5m; Connectors: NC3FXX-B & NC3MXX-B	1039630
NKX3D122-X1X1-M1000	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 10m; Connectors: NC3FXX-B & NC3MXX-B	1039631
NKX3D122-X1X1-M1500	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 15m; Connectors: NC3FXX-B & NC3MXX-B	1039632

NKX3D122-X1X1-M2000	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 20m; Connectors: NC3FXX-B & NC3MXX-B	1039633
NKX3D134-X1X1-M0100	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 1m; Connectors: NC3FXX-B & NC3MXX-B	1039634
NKX3D134-X1X1-M0150	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 1.5m; Connectors: NC3FXX-B & NC3MXX-B	1039635
NKX3D134-X1X1-M0300	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 3m; Connectors: NC3FXX-B & NC3MXX-B	1039636
NKX3D134-X1X1-M0500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 5m; Connectors: NC3FXX-B & NC3MXX-B	1039637
NKX3D134-X1X1-M1000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 10m; Connectors: NC3FXX-B & NC3MXX-B	1039638
NKX3D134-X1X1-M1500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 15m; Connectors: NC3FXX-B & NC3MXX-B	1039639
NKX3D134-X1X1-M2000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 20m; Connectors: NC3FXX-B & NC3MXX-B	1039640
NKX3D134-X1X1-M2500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 25m; Connectors: NC3FXX-B & NC3MXX-B	1039641
NKX3D134-X1X1-M3000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 30m; Connectors: NC3FXX-B & NC3MXX-B	1039642
NKX3D134-X1X1-M4000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 40m; Connectors: NC3FXX-B & NC3MXX-B	1039643

M4000		
	Connectors: NC3FXX-B & NC3MXX-B	
NKX3D134-X1X1-M5000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 50m; Connectors: NC3FXX-B & NC3MXX-B	1039644
NKX5D122-X2X2-M0050	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 0.5m; Connectors: NC5FXX-B & NC5MXX-B	1039645
NKX5D122-X2X2-M0100	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 1m; Connectors: NC5FXX-B & NC5MXX-B	1039646
NKX5D122-X2X2-M0150	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 1.5m; Connectors: NC5FXX-B & NC5MXX-B	1039647
NKX5D122-X2X2-M0300	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 3m; Connectors: NC5FXX-B & NC5MXX-B	1039648
NKX5D122-X2X2-M0500	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 5m; Connectors: NC5FXX-B & NC5MXX-B	1039649
NKX5D122-X2X2-M1000	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 10m; Connectors: NC5FXX-B & NC5MXX-B	1039650
NKX5D122-X2X2-M1500	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 15m; Connectors: NC5FXX-B & NC5MXX-B	1039651
NKX5D122-X2X2-M2000	Cable: PROFESSIONAL DMX AES / EBU Foil + Braided Shield, 2 x 0.22 mm ² / AWG 24 20m; Connectors: NC5FXX-B & NC5MXX-B	1039652
NKX5D134-X2X2-M0100	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 1m; Connectors: NC5FXX-B & NC5MXX-B	1039653

NKX5D134-X2X2-M0150	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 1.5m; Connectors: NC5FXX-B & NC5MXX-B	1039654
NKX5D134-X2X2-M0300	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 3m; Connectors: NC5FXX-B & NC5MXX-B	1039655
NKX5D134-X2X2-M0500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 5m; Connectors: NC5FXX-B & NC5MXX-B	1039656
NKX5D134-X2X2-M1000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 10m; Connectors: NC5FXX-B & NC5MXX-B	1039657
NKX5D134-X2X2-M1500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 15m; Connectors: NC5FXX-B & NC5MXX-B	1039658
NKX5D134-X2X2-M2000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 20m; Connectors: NC5FXX-B & NC5MXX-B	1039659
NKX5D134-X2X2-M2500	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 25m; Connectors: NC5FXX-B & NC5MXX-B	1039660
NKX5D134-X2X2-M3000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 30m; Connectors: NC5FXX-B & NC5MXX-B	1039661
NKX5D134-X2X2-M4000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 40m; Connectors: NC5FXX-B & NC5MXX-B	1039662
NKX5D134-X2X2-M5000	Cable: PROFESSIONAL DMX AES / EBU Spiral Shield, 2 x 0.34 mm ² / AWG 22 50m; Connectors: NC5FXX-B & NC5MXX-B	1039663

NKX3* / NKX5*



Article Naming

N K X 3 D 1 2 2 - X 1 X 1 - M 0 0 5 0


NEUTRIK XLR CABLE		LENGTH	
CONNECTOR TYPE			
3	3 Pin Connectors	M0050	0.5 m
5	5 Pin Connectors	M0100	1 m
CABLE TYPE		M0150	1.5 m
D1	1 DMX Channel (PVC Sheath)	M0300	3 m
D2	2 DMX Channels (PVC Sheath)	M0500	5 m
TD1	1 DMX Channel (PUR Sheath - TOP)	M1000	10 m
TD2	2 DMX Channels (PUR Sheath - TOP)	M1500	15 m
CROSS SECTION TYPE		M2000	20 m
22	0.22mm ² Cross Section Wires	M2500	25 m
34	0.34mm ² Cross Section Wires.	M3000	30 m
CONNECTOR COMBINATION		M4000	40 m
X1X1	NC3FXX-B / NC3MXX-B	M5000	50 m
X2X2	NC5FXX-B / NC5MXX-B	UNIT OF LENGTH	
		Metric	in m

6.5 mm
+/- 0.15

1.4 mm
+/- 0.05

Legend:

- 1 Jacket
- 2 Shield, braided 16/4/0.10
- 3 AL-PT Foil, AL side towards conductors.
- 4 Conductor Insulation
- 5 Conductor
- 6 Drain wire 7/0.2



Technical Information

Product	
Title	Profesional DMX AES/EBU Cables Assemblies (NKX*D1*-X*X*-M*)
Product group	premium DATA CABLES
Product family	DATA CABLES
Connection type	NEUTRIK® XLR

Electrical	
Characteristical impedance	120 Ω @ 1 kHz (nominal)
Attenuation	2.0 dB/100 m @ 1 MHz (nominal)
Capacitance	Cable conductor to conductor: 55 pF/m @ 1 kHz Cable conductor to shield: 110 pF/m @ 1 kHz 3 Pin connector contact to contact: ≤ 4 pF 5 Pin connector contact to contact: ≤ 7
Conductor resistance	0.22 mm ² /AWG 24: ≤ 80 m Ω /m @ 20 °C (nominal) 0.34 mm ² /AWG 22: ≤ 55 m Ω /m @ 20 °C (nominal)
Contact resistance	≤ 3 m Ω
Insulation resistance	Cable: > 1 G Ω /m @ 20 °C, 500 VDC Connector: > 10 G Ω (initial)
Dielectric strenght	Cable conductor to screen: 1000 VAC @ 50 Hz, 1 minute Connector: 1.5 kVDC

Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	min. 1000 mating cycles
Locking device	Latch lock
Minium bending radius	approx. 65 mm
Wiring	Soldered
Composition of conductor	0.22 mm ² / AWG 24: 7 x 0.20 mm OFC 0.34 mm ² / AWG 22: 19 x 0.15 mm OFC
Composition of drain wire	7 x 0.20 mm OFC (0.22 mm ² / AWG 24 only)
Shielding	0.22 mm ² / AWG 24: Foil + Braided (≥60%) 0.34 mm ² / AWG 22: Spiral (≥95%)
Overall diameter	6.5 +/- 0.15 mm

Material	
Wire	Annealed copper
Wire Insulation	Foamed PE
Drain Wire	Tinned copper (0.22 mm ² / AWG 24 only)
Filler	Cotton (0.34 mm ² / AWG 22 only)
Shield	0.22 mm ² / AWG 24: AL/PT Foil + Tined Copper 0.34 mm ² / AWG 22: Tinned Copper
Outer Jacket	PVC
Connector	See datasheets of NEUTRIK® NC3FXX-B, NC3MXX-B, NC5FXX-B, NC5MXX-B

Environmental	
Standard compliance	DMX512 / DMX512-A according to ANSI E1.11 AES/EBU according to AES3 RoHS according to 2011/65/EU
Ingress protection class	IP20
Temperature range	Mobile -10 °C to +70 °C Fixed: -20 °C to +70 °C